



Hyosung J440

QMFZ2 Component – Plastics		Friday, October 24, 2003				E163907			
HYOSUNG CORP									
PP DIV 450 KONGDUK–DONG MAPO–KU SEOUL 121–720 KOREA									
Material Designation: <b>J(a)40</b>									
Product Description: Polypropylene (PP), furnished as pellets, powder.									
Color	Min. Thick. (mm)	Flame Class	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI	
ALL	1.5	HB	-	65	65	65	-	-	
	CTI: -	HVTR: -		D495: -			IEC Ball Pressure(°C): -		
Dielectric Strength(kV/mm): -		Volume Resistivity(10 <sup>10</sup> ohm-cm): -					Dimensional Stability(%): -		
ISO Tensile Strength(MPa): -		ISO Flexural Strength(MPa): -					ISO Heat Deflection(°C): -		
ISO Tensile Impact(kJ/m <sup>2</sup> ): -		ISO Izod Impact(kJ/m <sup>2</sup> ): -					ISO Charpy Impact(kJ/m <sup>2</sup> ): -		
(a) Represents 3 through 7 incl.									
Report Date: 10/25/1994			Underwriters Laboratories Inc®						
UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.									