



Hyosung J640

QMFZ2 Component – Plastics		Friday, October 24, 2003				E163907			
HYOSUNG CORP									
PP DIV 450 KONGDUK-DONG MAPO-KU SEOUL 121-720 KOREA									
Material Designation: J(a)40									
Product Description: Polypropylene (PP), furnished as pellets, powder.									
Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	HB	-	-	65	65	65	-	-
CTI: -		HVTR: -		D495: -		IEC Ball Pressure(°C): -			
Dielectric Strength(kV/mm): -		Volume Resistivity(10 ¹⁰ ohm-cm): -				Dimensional Stability(%): -			
ISO Tensile Strength(MPa): -		ISO Flexural Strength(MPa): -				ISO Heat Deflection(°C): -			
ISO Tensile Impact(kJ/m ²): -		ISO Izod Impact(kJ/m ²): -				ISO Charpy Impact(kJ/m ²): -			
(a) Represents 3 through 7 incl.									
Report Date: 10/25/1994					Underwriters Laboratories Inc®				
UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.									