



Hyosung J945

QMFZ2 Component – Plastics			Friday, October 24, 2003				E163907			
HYOSUNG CORP										
PP DIV 450 KONGDUK-DONG MAPO-KU SEOUL 121-720 KOREA										
Material Designation: J945										
Product Description: Polypropylene (PP), furnished as pellets, powder.										
Color	Min. Thick. (mm)	Flame Class	HAI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWF1	
ALL	1.5	HB	-	-	65	65	65	-	-	
	CTI: -	HVTR: -			D495: -			IEC Ball Pressur(°C): -		
Dielectric Strength(kV/mm): -		Volume Resistivity(10 ¹⁰ ohm-cm): -				Dimensional Stability(%): -				
ISO Tensile Strength(MPa): -		ISO Flexural Strength(MPa): -				ISO Heat Deflection(°C): -				
ISO Tensile Impact(kJ/m ²): -		ISO Izod Impact(kJ/m ²): -				ISO Charpy Impact(kJ/m ²): -				
Report Date: 10/25/1994				Underwriters Laboratories Inc®						
UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.										